



### TECHNICAL FEATURES

OVERALL LENGHT	5.2 m	TUBE DIAMETER	46 cm
INSIDE LENGHT	4.2 m	NUMBER OF CHAMBERS	5
OVERALL BEAM	2.4 m	MAXIMUM ALLOWED POWE	100,00
INTERNAL BEAM	1.3 m	MAXIMUM ENGINE WEIGHT	150 Kg
BEAM (DEFLATED)	1.5 m	SHAFT	508 mm
HULL LENGHT	4.2 m	FUEL TANK	62 L
HULL WIDTH	1.5 m	MAX SPEED RANGE	50 KN
HULL HEIGHT	0,00	CONSTRUCTION	Deep V
DEADRISE	23°	CLASSIFICATION CEProof	C - RIB type IX
WEIGHT	400 Kg	NUMBER OF PASSENGERS	6

### STANDARD EQUIPMENT

**CORED HULL, BRACES AND DECK**  
**NON SLIP DECK**  
**DECK WELL AND DRAIN TRUNKS**  
**UNDER DECK CABLING**  
**HULL STERN DRAIN PLUG**

**INFLATABLES FULLY HOT AIR WELDED**  
**EXTERNAL LIFE LINES**  
**HD D RUBBING STRAKE**  
**BOW U BOLT**

### OPTIONAL EQUIPMENT

**FOREDECK LOCKER**  
**JOCKEY CONSOLE**  
**MASTER HELM COMPACT CONSOLE**  
**LIFTING POINTS**

**SUSPENSION SEAT**  
**TOWING POLE**  
**BOARDING PANELS**

VORTEQ reserves the right to modify the characteristics of its products without prior notice (tolerance 5% on dimensions, weight and speed).  
 VORTEQ, TM is a registered trademark – Copyright VORTEQ, TM. This document cannot be considered as a contractual document. Non-contractual pictures.

VORTEQ RIBS are manufactured in Portugal by DIVEXPRO LDA - Zona Industrial Vale do Grou P2 - 2525-079 Atouguia da Baleia - Portugal

info@divexpro.com | www.divexpro.com