



TECHNICAL FEATURES

OVERALL LENGHT	5.6 m	TUBE DIAMETER	48 cm
INSIDE LENGHT	4.6 m	NUMBER OF CHAMBERS	5
OVERALL BEAM	2.4 m	MAXIMUM ALLOWED POWE	100 HP
INTERNAL BEAM	1.4 m	MAXIMUM ENGINE WEIGHT	150 Kg
BEAM (DEFLATED)	1.6 m	SHAFT	508 mm
HULL LENGHT	4.6 m	FUEL TANK	62 L
HULL WIDTH	1.5 m	MAX SPEED RANGE	50 KN
HULL HEIGHT	55 cm	CONSTRUCTION	Deep V
DEADRISE	23°	CLASSIFICATION CEProof	C - RIB type IX
WEIGHT	400 Kg	NUMBER OF PASSENGERS	6

STANDARD EQUIPMENT

CORED HULL, BRACES AND DECK
 NON SLIP DECK
 DECK WELL AND DRAIN TRUNKS
 UNDER DECK CABLING
 HULL STERN DRAIN PLUG

INFLATABLES FULLY HOT AIR WELDED
 EXTERNAL LIFE LINES
 HD D RUBBING STRAKE
 BOW U BOLT

OPTIONAL EQUIPMENT

FOREDECK LOCKER
 JOCKEY CONSOLE
 MASTER HELM COMPACT CONSOLE
 LIFTING POINTS

SUSPENSION SEAT
 TOWING POLE
 BOARDING PANELS

VORTEQ reserves the right to modify the characteristics of its products without prior notice (tolerance 5% on dimensions, weight and speed).
 VORTEQ, TM is a registered trademark – Copyright VORTEQ, TM. This document cannot be considered as a contractual document. Non-contractual pictures.

VORTEQ RIBS are manufactured in Portugal by DIVEXPRO LDA - Zona Industrial Vale do Grou P2 - 2525-079 Atouguia da Baleia - Portugal

info@divexpro.com | www.divexpro.com