



TECHNICAL FEATURES

OVERALL LENGHT	8.3 m	TUBE DIAMETER	52 CM
INSIDE LENGHT	7.3 m	NUMBER OF CHAMBERS	7
OVERALL BEAM	2.85 m	MAXIMUM ALLOWED POWE	400 HP
INTERNAL BEAM	1.75 m	MAXIMUM ENGINE WEIGHT	0,00
BEAM (DEFLATED)	2.3 m	SHAFT	1 x 762mm 2 x 635mm
HULL LENGHT	7.3 m	FUEL TANK	300 L
HULL WIDTH	2.45 m	MAX SPEED RANGE	60 Kn
HULL HEIGHT	80 cm	CONSTRUCTION	Deep V
DEADRISE	23°	CLASSIFICATION CEProof	C - RIB type IX
WEIGHT	900 Kg	NUMBER OF PASSENGERS	12

STANDARD EQUIPMENT

CORED HULL, BRACES AND DECK
NON SLIP DECK
DECK WELL AND DRAIN TRUNKS
UNDER DECK CABLING
HULL STERN DRAIN PLUG

INFLATABLES FULLY HOT AIR WELDED
EXTERNAL LIFE LINES
HD D RUBBING STRAKE
BOW U BOLT

OPTIONAL EQUIPMENT

FOREDECK LOCKER
PATROL CONSOLE COMPACT
PATROL CONSOLE EXPEDITION
LIFTING POINTS

SUSPENSION SEATS
NAVIGATION FRAME
BOARDING PANELS
RAISED DECK

VORTEQ reserves the right to modify the characteristics of its products without prior notice (tolerance 5% on dimensions, weight and speed).
 VORTEQ TM is a registered trademark – Copyright VORTEQ TM. This document cannot be considered as a contractual document. Non-contractual pictures.

VORTEQ RIBS are manufactured in Portugal by DIVEXPRO LDA - Zona Industrial Vale do Grou P2 - 2525-079 Atouguia da Baleia - Portugal

info@divexpro.com | www.divexpro.com