



### TECHNICAL FEATURES

OVERALL LENGHT	9.3 m	TUBE DIAMETER	52 cm
INSIDE LENGHT	8.3 m	NUMBER OF CHAMBERS	7
OVERALL BEAM	2.9 m	MAXIMUM ALLOWED POWE	600 HP
INTERNAL BEAM	1.8 m	MAXIMUM ENGINE WEIGHT	600 Kg
BEAM (DEFLATED)	2.4 m	SHAFT	1 x 762mm   2 x 635mm
HULL LENGHT	8.3 m	FUEL TANK	300 L
HULL WIDTH	2.5 m	MAX SPEED RANGE	60 miles
HULL HEIGHT	80 cm	CONSTRUCTION	Deep V
DEADRISE	23°	CLASSIFICATION CEProof	C - RIB type IX
WEIGHT	1100 Kg	NUMBER OF PASSENGERS	14

### STANDARD EQUIPMENT

**CORED HULL, BRACES AND DECK**  
**NON SLIP DECK**  
**DECK WELL AND DRAIN TRUNKS**  
**UNDER DECK CABLING**  
**HULL STERN DRAIN PLUG**

**INFLATABLES FULLY HOT AIR WELDED**  
**EXTERNAL LIFE LINES**  
**RUBBING STRAKE**  
**BOW U BOLT**

### OPTIONAL EQUIPMENT

**FOREDECK LOCKER**  
**PATROL CONSOLE COMPACT**  
**PATROL CONSOLE EXPEDITION**  
**LIFTING POINTS**

**SUSPENSION SEATS**  
**NAVIGATION FRAME**  
**BOARDING PANELS**  
**RAISED DECK**

VORTEQ reserves the right to modify the characteristics of its products without prior notice (tolerance 5% on dimensions, weight and speed).  
 VORTEQ TM is a registered trademark – Copyright VORTEQ TM. This document cannot be considered as a contractual document. Non-contractual pictures.

VORTEQ RIBS are manufactured in Portugal by DIVEXPRO LDA - Zona Industrial Vale do Grou P2 - 2525-079 Atouguia da Baleia - Portugal

info@divexpro.com | www.divexpro.com