



TECHNICAL FEATURES

OVERALL LENGHT	12 m	TUBE DIAMETER	0,00
INSIDE LENGHT	11 m	NUMBER OF CHAMBERS	0
OVERALL BEAM	3.4 m	MAXIMUM ALLOWED POWE	800,00
INTERNAL BEAM	2.1 m	MAXIMUM ENGINE WEIGHT	900 Kg
BEAM (DEFLATED)	2.8 m	SHAFT	1 x 762mm 2 x 635mm
HULL LENGHT	11 m	FUEL TANK	450 L
HULL WIDTH	2.6 m	MAX SPEED RANGE	60 miles
HULL HEIGHT	90 cm	CONSTRUCTION	Deep V
DEADRISE	23°	CLASSIFICATION CEProof	C - RIB type IX
WEIGHT	0,00	NUMBER OF PASSENGERS	24

STANDARD EQUIPMENT

CORED HULL, BRACES AND DECK	INFLATABLES FULLY HOT AIR WELDED
NON SLIP DECK	EXTERNAL LIFE LINES
DECK WELL AND DRAIN TRUNKS	RUBBING STRAKE
UNDER DECK CABLING	BOW U BOLT
HULL STERN DRAIN PLUG	

OPTIONAL EQUIPMENT

FOREDECK LOCKER	SUSPENSION SEATS
PATROL CONSOLE COMPACT	NAVIGATION FRAME
PATROL CONSOLE EXPEDITION	BOARDING PANELS
LIFTING POINTS	RAISED DECK

VORTEQ reserves the right to modify the characteristics of its products without prior notice (tolerance 5% on dimensions, weight and speed).
 VORTEQ TM is a registered trademark – Copyright VORTEQ TM. This document cannot be considered as a contractual document. Non-contractual pictures.

VORTEQ RIBS are manufactured in Portugal by DIVEXPRO LDA - Zona Industrial Vale do Grou P2 - 2525-079 Atouguia da Baleia - Portugal

info@divexpro.com | www.divexpro.com